



JUNCTION BOX

Abox 160-16²



Abox 160-16²

Junction box

CUSTOMIZABLE

180 x 180 x 91 mm
Article number: 81641001

Junction box acc. to DIN EN 60670 (VDE 0606), Ui=690V, with IP54 attachment bushes, with blanking plug M40, Seal range 17 - 30 mm, with sealing kit

Grey, with high-set screw terminal, 5-pole - 16 mm² (4 x 6² / 4 x 10² / 4 x 16²)



Technical data

Measures

Width:	180 mm
Length:	180 mm
Height:	91 mm

Material

Base:	Polystyrene
Cover:	Polystyrene

Certificates



Accessory

- Abox 160 KLS-16² - Terminal block
- KS M25-gro - Combi set
- KST M25-33 - Combi connector
- KST M25-17 - Combi connector
- Abox 160 MPI - Mounting plate
- AST M25 - Attachment bushes
- AST M32 - Attachment bushes
- AST M40 - Attachment bushes
- BST M20 - Ventilation seal
- DMS M20 - Double-membrane seals
- DMS M25 - Double-membrane seals
- DMS M32 - Double-membrane seals
- DMS M32/4 - Double-membrane seals



JUNCTION BOX

Abox 160-16²

Other attributes

Entries:	12
Rated cross section:	16 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V
Explosion safety:	none
Functional integrity:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
Weatherproof:	No

KS M20 - Combi set

KS M25 - Combi set

KS M32 - Combi set

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%