



JUNCTION BOX

Abox 060-6²



Abox 060-6²

Junction box

CUSTOMIZABLE

110 x 110 x 67 mm
Article number: 80640701

Junction box acc. to DIN EN 60670 (VDE 0606), Ui=690V, with IP54 attachment bushes, with blanking plug M25, seal range 9 - 18.5 mm

Grey, with high-set screw terminal, 5-pole - 6 mm² (4 x 2.5² / 4 x 4² / 3 x 6²)



Technical data

Measures

Width:	110 mm
Length:	110 mm
Height:	67 mm

Material

Base:	Polystyrene
Cover:	Polystyrene

Certificates



Accessory

- Abox 060 KLS-6² - Terminal block
- KS M25-gro - Combi set
- Abox 060 MPI - Mounting plate
- Abox PST - Sealing kit
- AST M20 - Attachment bushes
- AST M25 - Attachment bushes
- BST M20 - Ventilation seal
- DMS M20 - Double-membrane seals
- DMS M20/sw - Double-membrane seals
- DMS M25 - Double-membrane seals
- GMU PA M20 - Lock nut
- GMU PA M25 - Lock nut
- GMU PG 16-M20 - Lock nut



JUNCTION BOX

Abox 060-6²

Other attributes

Entries:	9
Rated cross section:	6 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V
Explosion safety:	none
Functional integrity:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equiquest:	Terminal
Color:	Grey

KS M20 - Combi set

KS M25 - Combi set

KVR M20-GDB/MGM - Cable gland

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%